



EVEN OUR SMALLEST TRACTOR STILL PACKS A BIG PUNCH.





10 SERIES



TRACTOR MODEL	1022	1025
TRACTOR MODEL	1022	1025
TYPE	3 CYLINDER, WATER COOLED, DIESEL	3 CYLINDER, WATER COOLED, DIESEL
ENGINE HP @ RPM	21.5	24.6
DISPLACEMENT (IN.)	60.6	77.3
NUMBER OF CYLINDERS	3	3
FUEL TANK (GAL.)	6.6	5.8
DRIVE TRAIN		
TRANSMISSION	HST	HST
NUMBER OF SPEEDS	2 RANGE	2 RANGE
CLUTCH	NO	NO
BRAKES	WET, MULTI-DISC	WET, MULTI-DISC
PTO		
TYPE	INDEPENDENT	INDEPENDENT
REAR(MID) PTO SPEED	540)	540
PTO HP	15.4	18.8
HYDRAULICS		
TYPE	HYDROSTATIC POWER STEERING	HYDROSTATIC POWER STEERING
TOTAL HYDRAULIC FLOW (POWER STEERING+IMPLEMENT)	6.3 (2.1+4.2) / 23.8 (8+15.8)	7.0 (2.8+4.2) / 25.7 (10.5+15.8)
3-POINT HITCH	LIMITED CAT 1	CAT I
REAR REMOTE VALVE	OPTIONAL (UP TO 1)	N/A
3POINT HITCH LIFT CAPACITY (LBS.) @24" BEHIND LIFT POINT @ BALL ENDS	499	499
ELECTRICAL		
BATTERY	12 V, 500 CCA	12 V, 500 CCA
ALTERNATOR	12 V, 40 A	12 V, 40 A
DIMENSIONS		
OVERALL LENGTH (IN.)	94.2	104
OVERALL WIDTH (IN.)	44.5	45.8
OVERALL HEIGHT (IN.)	86.6	91.3
WHEELBASE (IN.)	53.1	57.5
MINIMUM GROUND CLEARANCE (IN.)	8.3	9.4
WEIGHT LBS(KG)	1433	1638
WHEELS & TIRES		
IND (FRONT)	18X8.50-10	23X8.5-12
IND (REAR)	26X12-12	12-16.50
LOADER MODEL	BBL100	BBL105
STANDARD BUCKET SIZE (IN.)	48	50
MAXIMUM LIFT HEIGHT (IN.)	72.7	75.5
DIG DEPTH (IN.)	4.0	4.6
LIFT CAPACITY TO FULL HEIGHT AT PIVOT PIN (LBS.)	617	992
BREAKOUT FORCE (LBS.)	1253	1531
SHIPPING WEIGHT (LBS.)	438	573
BACKHOE MODEL	BBH100	BBH105
STANDARD BUCKET SIZE (IN.)	12	12
TYPE	SUBFRAME-MOUNTED, QUICK ATTACH	SUBFRAME-MOUNTED, QUICK ATTACH
MAXIMUM DIG DEPTH (IN.)	66	76
DIG FORCE BUCKET (LBS.)	1975	2020
SHIPPING WEIGHT (LBS.)	747	816

SPECIFICATIONS SUBJECT TO CHANGE

YOUR EXCLUSIVE DEALER:

BAD BOY
TRACTORS

WORK WITH AN *Attitude*

www.badboytractors.com • 102 Industrial Drive • Batesville, AR 72501